



FC Fiber Connector: FC/PC(UPC,APC)/SM(MM) Φ 0.9(2.0/3.0)

Specification:	Vibration:10~58Hz / Amplitude:1.5mm / Temp:-40°C~75°C	
Fiber Mode:	Single Mode Fiber (SM)	Multi Mode Fiber (MM)
Fiber Dia:	Φ 0.9mm , Φ 2.0mm , Φ 3.0mm	Φ 0.9mm , Φ 2.0mm , Φ 3.0mm
Insertion Loss:	PC $\leq$ 0.2,UPC $\leq$ 0.2,APC $\leq$ 0.3 dB	PC $\leq$ 0.3 dB
Return Loss:	PC $\geq$ 40,UPC $\geq$ 50,APC $\geq$ 60 dB	N/A



ST Fiber Connector: ST/PC(UPC,APC)/SM(MM) Φ 0.9(2.0/3.0)

Specification:	Vibration:10~58Hz / Amplitude:1.5mm / Temp:-40°C~75°C	
Fiber Mode:	Single Mode Fiber (SM)	Multi Mode Fiber (MM)
Fiber Dia:	Φ 0.9mm , Φ 2.0mm , Φ 3.0mm	Φ 0.9mm , Φ 2.0mm , Φ 3.0mm
Insertion Loss:	PC $\leq$ 0.2,UPC $\leq$ 0.2,APC $\leq$ 0.3 dB	PC $\leq$ 0.3 dB
Return Loss:	PC $\geq$ 40,UPC $\geq$ 50,APC $\geq$ 60 dB	N/A



SC Fiber Connector: SC/PC(UPC,APC)/SM(MM) Φ 0.9(2.0/3.0)

Specification:	Vibration:10~58Hz / Amplitude:1.5mm / Temp:-40°C~75°C	
Fiber Mode:	Single Mode Fiber (SM)	Multi Mode Fiber (MM)
Fiber Dia:	Φ 0.9mm , Φ 2.0mm , Φ 3.0mm	Φ 0.9mm , Φ 2.0mm , Φ 3.0mm
Insertion Loss:	PC $\leq$ 0.2,UPC $\leq$ 0.2,APC $\leq$ 0.3 dB	PC $\leq$ 0.3 dB
Return Loss:	PC $\geq$ 40,UPC $\geq$ 50,APC $\geq$ 60 dB	N/A



LC Fiber Connector: LC/PC(UPC,APC)/SM(MM) Φ 0.9(2.0/3.0)

Specification:	Vibration:10~58Hz / Amplitude:1.5mm / Temp:-40°C~75°C	
Fiber Mode:	Single Mode Fiber (SM)	Multi Mode Fiber (MM)
Fiber Dia:	Φ 0.9mm , Φ 2.0mm , Φ 3.0mm	Φ 0.9mm , Φ 2.0mm , Φ 3.0mm
Insertion Loss:	PC $\leq$ 0.2,UPC $\leq$ 0.2,APC $\leq$ 0.3 dB	PC $\leq$ 0.3 dB
Return Loss:	PC $\geq$ 40,UPC $\geq$ 50,APC $\geq$ 60 dB	N/A



MU Fiber Connector: MU/PC(UPC)/SM(MM) Φ 0.9(2.0/3.0)

Specification:	Vibration:10~58Hz / Amplitude:1.5mm / Temp:-40°C~75°C	
Fiber Mode:	Single Mode Fiber (SM)	Multi Mode Fiber (MM)
Fiber Dia:	Φ 0.9mm , Φ 2.0mm , Φ 3.0mm	Φ 0.9mm , Φ 2.0mm , Φ 3.0mm

Insertion Loss:	PC≤0.2,UPC≤0.2 dB	PC≤0.3 dB
Return Loss:	PC≥40,UPC≥50 dB	N/A

.....

MTRJ Fiber Connector: MTRJ/PC/SM(MM)Φ0.9(2.0/3.0)



Specification:	Vibration:10~58Hz / Amplitude:1.5mm / Temp:-40°C~75°C	
Fiber Mode:	Single Mode Fiber (SM)	Multi Mode Fiber (MM)
Fiber Dia:	Φ0.9mm , Φ2.0mm , Φ3.0mm	Φ0.9mm , Φ2.0mm , Φ3.0mm
Insertion Loss:	PC≤0.2 dB	PC≤0.3 dB
Return Loss:	PC≥40 dB	N/A